

Appl. No. 10/788,757

Amdt. Dated October 6, 2005

Reply to Office Action of August 4, 2005

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the above-identified application:

Claim 1 (Original) An air turbine starter, comprising:

a starter housing adapted to couple to a gearbox assembly, the starter housing including a supply opening and an exhaust opening, each configured to provide fluid communication between the gearbox assembly and the starter housing;

a receptacle coupled to the starter housing proximate the supply opening to thereby define a reservoir;

a first valve disposed within the reservoir and configured to open or close the supply opening in response to a pressure differential between the starter housing and the gearbox assembly; and

a second valve coupled to the starter housing proximate the exhaust opening and configured to open or close the exhaust opening in response to the pressure differential between the starter housing and the gearbox assembly.

Claim 2 (Original) The air turbine starter of claim 1, wherein the first and second valves each comprise:

a valve flexure, at least a portion of which is coupled to the starter housing, the valve flexure configured to selectively move between a valve open and valve close position in response to the pressure differential between the starter housing and the gearbox.

Claim 3 (Original) The air turbine starter of claim 2, wherein the valve flexure has a curve, wherein the curve curves away from the starter housing.

Claim 4 (Original) The air turbine starter of claim 3, further comprising:

Appl. No. 10/788,757

Amdt. Dated October 6, 2005

Reply to Office Action of August 4, 2005

a stop coupled to the starter housing and configured to provide a biasing force on the valve flexure to bias the valve flexure in an open position.

Claim 5 (Original) The air turbine starter of claim 3, further comprising:

a stop coupled to the receptacle and configured to provide a biasing force on the valve flexure to bias the valve flexure in an open position.

Claim 6 (Original) The air turbine starter of claim 2, wherein the valve flexure comprises a leaf spring.

Claim 7 (Original) The air turbine starter of claim 2, wherein the valve flexure comprises spring steel

Claim 8 (Original) The air turbine starter of claim 2, further comprising:

a first and a second valve seat each coupled to the starter housing concentric to the supply and exhaust openings and configured to selectively contact each of the valve flexures to provide a leak tight seal when the valve flexures are in the valve close position.

Claim 9 (Original) The air turbine starter of claim 8, wherein at least a portion of the valve seat configured to contact the valve flexure includes sharp edges.

Claim 10 (Original) The air turbine starter of claim 1 wherein the receptacle comprises a standpipe.

Claim 11 (Original) The air turbine starter of claim 1, further comprising:

a supply line in fluid communication with the reservoir, the supply line configured to supply fluid from the gearbox to the starter housing.

Appl. No. 10/788,757

Amdt. Dated October 6, 2005

Reply to Office Action of August 4, 2005

Claim 12 (Original) The air turbine starter of claim 11, wherein the fluid supply line is further configured to supply a continuous flow of fluid from the gearbox to the starter housing.

Claim 13 (Currently Amended) A check valve assembly for placement proximate an opening in a wall separating a first environment and a second environment, the check valve assembly comprising:

a valve flexure, at least a portion of which is coupled to the wall proximate the opening and configured to be biased to a valve open position and to selectively move between [[a]] the valve open position and a valve close position in response to the pressure differential between the first and second environments; [[and ]]

a valve seat coupled to the wall concentric to the opening and configured to selectively contact the valve flexure to provide a leak tight seal when the valve flexure is in [[a]] the valve close position; and

a stop disposed proximate the valve flexure and configured to contact the valve flexure when the valve flexure is in the valve open position.

Claim 14 (Original) The check valve assembly of claim 13, wherein the valve flexure comprises a leaf spring.

Claim 15 (Original) The check valve assembly of claim 13, wherein the valve flexure comprises spring steel.

Claim 16 (Original) The check valve assembly of claim 13, wherein the valve flexure comprises rubber.

Claim 17 (Currently Amended) The check valve assembly of claim 13, wherein the ~~further comprising:~~

Appl. No. 10/788,757

Amdt. Dated October 6, 2005

Reply to Office Action of August 4, 2005

a stop is coupled to the receptacle and configured to provide a biasing force on the valve flexure to bias the valve flexure to the open position.

Claim 18 (Currently Amended) The check valve assembly of claim 13, wherein the further comprising:

a stop is coupled to the wall and configured to provide a biasing force on the valve flexure to bias the valve flexure in an open position.

Claim 19 (Original) The check valve assembly of claim 13, wherein at least a portion of the valve seat configured to contact the valve flexure includes sharp edges.

Claim 20 (Original) A system for providing fluid between a gearbox and an air turbine starter, the system comprising:

a starter housing positioned between and adapted to couple to a gearbox assembly and air turbine starter, the plate including a supply opening and an exhaust opening, each configured to provide fluid communication between the gearbox assembly and the air turbine starter;

a receptacle coupled to the starter housing proximate the supply opening to thereby define a reservoir;

a supply line in fluid communication with the reservoir, the supply line configured to supply fluid from the gearbox to the starter housing;

a first valve disposed within the reservoir and configured to open or close the supply opening in response to a pressure differential between the starter housing and the gearbox assembly; and

a second valve coupled to the starter housing proximate to the exhaust opening and configured to open or close the exhaust opening in response to the pressure differential between the starter housing and the gearbox assembly.

Appl. No. 10/788,757

Amdt. Dated October 6, 2005

Reply to Office Action of August 4, 2005

Claim 21 (Original) The system of claim 20, wherein the fluid supply line is further configured to supply a continuous flow of fluid from the gearbox to the starter housing.

Claim 22 (Original) The system of claim 20, wherein the first and second valves each further comprise:

a valve flexure having first and second sides, wherein the first side is coupled to the starter housing and the second side is configured to selectively move between a valve open and valve close position in response to the pressure differential between the starter housing and the gearbox.

Claim 23 (Original) The system of claim 22, wherein the valve flexure comprises a leaf spring.

Claim 24 (Original) The system of claim 22, wherein the valve flexure comprises spring steel.

Claim 25 (Original) The system of claim 22, wherein the valve flexure comprises rubber.

Claim 26 (Original) The system of claim 22, further comprising:

a valve seat coupled to the starter housing concentric to the opening and configured to selectively contact the valve flexure to provide a leak tight seal when the valve flexure is in a close position.

Claim 27 (Original) The system of claim 26, wherein at least a portion of the valve seat configured to contact the valve flexure includes sharp edges.

Claim 28 (Original) The system of claim 22, further comprising:

Appl. No. 10/788,757

Amdt. Dated October 6, 2005

Reply to Office Action of August 4, 2005

a stop coupled to the receptacle and configured to provide a biasing force on the valve flexure to bias the valve flexure to the valve open position.

Claim 29 (Original) The system of claim 22, further comprising:

a stop coupled to the starter housing and configured to provide a biasing force on the valve flexure to bias the valve flexure in an open position.